

Expect more from your floor.

Safety Data Sheet acc. to OSHA HCS

Printing date 04/27/2016 Reviewed on 04/27/2016

1: Identification

- · 1.1 Product identifier
- · Trade name: Silikal RE 42 (Component A)
- · Application of the substance / the preparation: Epoxy resin
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Silikal America 609-B Fertilla Street Carrolton, GA 30117 Tel.: 770.830.1404 Fax.: 777.830.9213 info@silikalamerica.com

- · Information department: Silikal America
- 1.4 Emergency telephone number: INFOTRAC 1-800-535-5053

2: Hazard(s) identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labeled according to the CLP regulation.

Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

Hexandioldiglycidether

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eve irritation.

H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves.

P280 Wear eye protection / face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 1 Reactivity = 0

Printing date 04/27/2016 Reviewed on 04/27/2016

Trade name: Silikal RE 42 (Component A)

· HMIS-ratings (scale 0 - 4)

(Contd. of page 1)



Health = 1 Fire = 1

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB**: Not applicable.

3: Composition/information on ingredients

- · 3.1 Chemical characterization: Substances
- · CAS No. Description

16096-31-4 Hexandioldiglycidether

- · Identification number(s)
- · EC number: 240-260-4
- · 3.2 Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

| · Dangerous components: | |
|--|----------|
| 16096-31-4 Hexandioldiglycidether | 50-100% |
| ♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317 | _ |
| 100-51-6 Benzyl alcohol | 0.5-2.5% |
| ① Acute Tox. 4, H302; Acute Tox. 4, H332 | - |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4: First-aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Take affected persons into fresh air and keep quiet.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Seek immediate medical advice.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

5: Fire-fighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.

(Contd. on page 3)

Printing date 04/27/2016 Reviewed on 04/27/2016

Trade name: Silikal RE 42 (Component A)

· Additional information

(Contd. of page 2)

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

· 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Keep receptacles tightly sealed.

- · Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Store in cool, dry conditions in well sealed receptacles.

Do not allow to enter sewers/ surface or ground water.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Maximum storage temperature: 25 °C
- · 7.3 Specific end use(s) No further relevant information available.

8: Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · 8.1 Control parameters

· Components with limit values that require monitoring at the workplace:

100-51-6 Benzyl alcohol

WEEL Long-term value: 10 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

Use suitable respiratory protective device only when aerosol or mist is formed.

Recommended filter device for short term use: Filter A

(Contd. on page 4)

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/27/2016 Reviewed on 04/27/2016

Trade name: Silikal RE 42 (Component A)

· Protection of hands:



· Material of gloves

Nitrile rubber, NBR Butyl rubber, BR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 3).

For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9: Physical and chemical properties

| 9.1 Information on basic physical ar General Information Appearance: | nd chemical properties |
|--|---|
| Form: | Fluid |
| Color: | Yellowish |
| 00.0.1 | |
| · Odor: | Characteristic |
| · Odor threshold: | Not determined. |
| · pH-value: | Not determined. |
| · Change in condition | |
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | > 200 °C (> 392 °F) |
| | |
| · Flash point: | 150 °C (302 °F) |
| · Flammability (solid, gaseous): | Not applicable. |
| · Ignition temperature: | |
| Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product does not present an explosion hazard. |
| · Explosion limits: | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| • | |
| · Vapor pressure at 50 °C (122 °F): | 5 hPa (4 mm Hg) |
| · Density at 20 °C (68 °F): | 1.06 g/cm3 (8.846 lbs/gal) |
| · Relative density ` | Not determined. |

(Contd. on page 5)

Printing date 04/27/2016 Reviewed on 04/27/2016

Trade name: Silikal RE 42 (Component A)

| | | (Contd. of page |
|--------------------------------------|--|-----------------|
| · Vapor density | Not determined. | |
| Evaporation rate | Not determined. | |
| · Solubility in / Miscibility with | | |
| Water: | Not miscible or difficult to mix. | |
| · Partition coefficient (n-octanol/w | ater): Not determined. | |
| · Viscosity: | | |
| Dynamic at 20 °C (68 °F): | 15 mPas | |
| Kinematic: | Not determined. | |
| · Solvent content: | | |
| Organic solvents: | 1.0 % | |
| Solids content: | 99.0 % | |
| · 9.2 Other information | No further relevant information available. | |

10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions Reacts with alcohols, amines, aqueous acids and alkalis.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Reacts with alkali, amines and strong acids.
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide
- · Additional information:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- Primary irritant effect:
- on the skin:

Causes skin irritation.

· on the eye:

Causes serious eye irritation.

· Sensitization:

May cause an allergic skin reaction.

- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

US

Printing date 04/27/2016 Reviewed on 04/27/2016

Trade name: Silikal RE 42 (Component A)

(Contd. of page 5)

12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation:

Must be specially treated adhering to official regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation:

Packaging can be reused or recycled after cleaning.

Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

| 4441111111 | | |
|---|-----------------|--|
| · 14.1 UN-Number | \/a:d | |
| · DOT, ADR, ADN, IMDG, IATA | Void | |
| · 14.2 UN proper shipping name | | |
| · DOT, ADR, ADN, IMDG, IATA | Void | |
| · 14.3 Transport hazard class(es) | | |
| · DOT, ADR, ADN, IMDG, IATA | | |
| · Class | Void | |
| · 14.4 Packing group | | |
| · DOT, ADR, IMDG, IATA | Void | |
| · 14.5 Environmental hazards: | | |
| · Marine pollutant: | No | |
| · 14.6 Special precautions for user | Not applicable. | |
| · 14.7 Transport in bulk according to Ann | ex II | |
| of MARPOL73/78 and the IBC Code | Not applicable. | |
| · UN "Model Regulation": | Void | |

US

Printing date 04/27/2016 Reviewed on 04/27/2016

Trade name: Silikal RE 42 (Component A)

(Contd. of page 6)

15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· AGW (German Workplace Threshold Value)

None of the ingredients is listed.

- National regulations:
- · Technical instructions (air):

| Class | Share in % |
|-------|------------|
| II | 0,5-2,5 |

- · Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Silikal America
- · Date of preparation / last revision 04/27/2016 / 16
- · Abbreviations and acronyms:

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

· * Data compared to the previous version altered.